

**Tender book to supply the following :
I- DRILL COLLAR**

Drill Collar

Roller (slic) drill collars according to API 7-1 spec 7G full length , heat-treated.

Made from chromium molybdenum alloy steel 4145 H as follows:

Item	Specifications	Unit	Qty
1	3 1/2"ODx1 1/2"ID (30-31)FT length 2 3/8"API IF (NC26) BOX up -2 3/8API IF(NC26) PIN down without slips and elevator recesses	single	20

Remarks

- 1- Each Drill Collar should equipped with internal & external cast steel thread protectors
- 2- Each Drill Collar and thread should be marked with API 7-1 monogram
- 3- Hardness of metal should be mentioned
- 4- All certificates of inspection are enclosed with shipment
- 5- All threads should be copper or phosphate plated
- 6- The manufacturing and country of origin must be mentioned in offer
- 7- Materials are new and unused
- 8- API-7-1& ISO certificates should be enclosed with the offer
- 9 - technical catalog or sheet should be enclosed with the offer with shipment
- 10- Mechanical test and analysis licenses for metal should be provide with shipment
- 11- Certificate issued by neutral international inspection company approved by the Syrian petroleum Company stating That the materials are conforming with specifications and API standards and tests specified in tender book with the shipment