

GROUP 1 - RIGHT HAND STRAIGHT SUBS

Q	LENGTH(INCH)	ID(INCH)	OD(INCH)	DESCRIPTION	
5	20	2 1/4	6 1/2	PIN 4 1/2 REG×BOX 4 1/2 IF	1
5	20	2 1/4	6 1/2	PIN 4 1/2 REG×BOX 4 IF	2
5	20	2 1/4	6 1/2	PIN 4 1/2 IF×BOX 4 1/2 IF	3
8	20	3	7 3/8	PIN 4 1/2 IF×BOX 5 1/2 FH	4
8	20	2 1/4	7 3/8	PIN 5 1/2 FH × PIN 4 1/2 IF	5
5	20	2 1/2	7 3/8	PIN 4 1/2 IF×BOX 4 IF	6
5	20	2 1/4	6 1/2	PIN 4 IF×BOX 4 1/2 IF	7
5	20	2 1/4	6 1/2	PIN 4 1/2 IF×BOX 7 5/8 REG	8
5	20	3	9	PIN 4 1/2 IF×BOX 4 1/2 FH	9
5	20	2 1/4	6 1/2	PIN 4 1/2 FH×BOX 4 1/2 IF	10
5	20	2 1/4	6 1/2	PIN 4 1/2 IF×BOX 6 5/8 REG	11
5	20	2 1/2	7 3/8	PIN 4 1/2 IF×BOX 3 1/2 IF	12
5	20	2 1/4	6 1/2	PIN 3 1/2 IF×BOX 4 1/2 IF	13
5	20	2 1/4	6 1/2	PIN 4 IF×BOX 3 1/2 IF	14
5	20	2 1/4	4 3/4	PIN 3 1/2 REG×BOX 3 1/2 IF	15
5	20	2 1/4	4 3/4	PIN 3 1/2 IF×BOX 3 1/2 REG	16
5	20	2 1/4	6 1/2	PIN 4 IF×BOX 3 1/2 FH	17
5	20	2 1/4	6 1/2	PIN 4 1/2 IF×BOX 3 1/2 FH	18
5	20	2 1/4	6 1/2	PIN 3 1/2 FH×BOX 4 1/2 IF	19
5	20	2 1/4	6 1/2	PIN 3 1/2 FH×BOX 4 IF	20
5	20	2	4 3/4	PIN 3 1/2 IF×BOX 3 1/2 FH	21
5	20	2	4 3/4	PIN 3 1/2 FH×BOX 3 1/2 IF	22
5	20	2	4 3/4	PIN 3 1/2 NC30×BOX 3 1/2 IF	23
5	20	2	4 3/4	PIN 3 1/2 IF×BOX 3 1/2 NC30	24
5	20	1 5/8	4 3/4	PIN 3 1/2 IF×BOX 2 7/8 IF	25
5	20	1 5/8	4 3/4	PIN 2 7/8 IF×BOX 3 1/2 IF	26
8	20	2 1/4	4 3/4	PIN 3 1/2 IF×BOX 3 1/2 IF	27
5	20	1 5/8	4 3/4	PIN 3 1/2 IF×BOX 2 3/8 IF	28
5	20	1 5/8	4 3/4	PIN 2 3/8 IF×BOX 3 1/2 IF	29
5	20	1 5/8	4 1/8	PIN 2 3/8 IF×BOX 2 7/8 IF	30
5	20	1 5/8	4	PIN 2 7/8 IF×BOX 2 3/8 IF	31
5	20	1 5/8	3 1/2	BOX 2 3/8 REG×BOX 2 3/8 IF	32
5	20	2 1/4	4 3/4	PIN 3 1/2 NU anceat×BOX 3 1/2 IF	33
5	20	3	6 1/2	PIN 3 1/2 NU anceat×BOX 4 1/2 IF	34
5	20	3	6 1/2	PIN 3 1/2 EUEupceat×BOX 4 1/2 IF	35
5	20	3	6 1/2	PIN 3 1/2 EUEupceat×BOX 3 1/2 IF	36
5	20	2 1/4	4 3/4	PIN 4 1/2 IF×BOX 4 1/2 vam top	37
5	20	3	6 1/2	PIN 4 1/2 vam top ×BOX 3 1/2 IF	38
5	20	3	5	PIN 3 1/2 VAM top×BOX 3 1/2 IF	39
5	20	1 3/4	4 3/4	PIN 4 1/2 B G T1×BOX 3 1/2 IF	40
5	20	3	4 3/4	PIN 3 1/2 IF×BOX 4 1/2 B G T1	41
5	20	3	4 3/4	PIN 3 1/2 VAM top×BOX 3 1/2 IF	42
5	20	3	4 3/4	PIN 2 3/8 EUE upceat×BOX 3 1/2 IF	43
5	20	2	4 3/4	PIN 2 3/8 B G T1×BOX 3 1/2 IF	44

GROUP 2- INCLINATION SUB

Q	LENGTH(INCH)	ID(INCH)	OD(INCH)	DESCRIPTION	INCLINATION	
2	20	2 1/2	9	PIN 6 5/8 REG×BOX 6 5/8 REG	3.5°	45
2	20	2 1/2	8	PIN 6 5/8 REG×BOX 6 5/8 REG	2.6°	46
2	20	2 1/4	6 3/4	PIN 4 1/2 IF×BOX 4 1/2 IF	2.5°	47
2	20	2	4 3/4	PIN 3 1/2 IF×BOX 3 1/2 IF	1.5°	48

GROUP 3 - SHORT DRILL PIPE- WRIGHT HAND				
Q	LENGTH(M)		DRSCRIPTION	
3	1	PIN 4 1/2 IF×BOX 4 1/2 IF	DRILL PIPE 5" , S135	1
3	2			
3	3			
3	4			
3	5			
3	6			
3	1	PIN 3 1/2 IF×BOX 3 1/2 IF	DRILL PIPE 3 1/2" , S135	2
3	2			
3	3			
3	4			
3	5			
3	6			

REMARKES

- 1- Right hand thread sube made from AISI4145 H modified alloy steel
- 2 - Fully heat treated inspection by ultra sonic all machined and finished acc to API standareds
- 3- Valid API -7-1 certificate should be enclosed with the offer
- 4 - Phosphate coated,lubricated and equiped with pressed steel threed protector
- 5 -Marking shall be done according API 7-1 , should be stamped with the manufactures name ,the API monogram , size and type of threads on the sub body
- 6 - Materials shall be new - not renewed and of new manufacture only
- 7 - Origin of Country and manufacturer must be mentioned with the offer
- 8- All above goods will be packed in to wooden cases